



X6-T982 Series IFPD

- UHD 3840X2160 (4K)
- Powered by Android 11
- High accuracy IR 20 touches
- Zero-bonding technology and double side AG glass
- Fast page sharing by scanning QR-Code
- Wireless screen sharing
- WiFi 6



4K

Resolution

20 Touches

Infrared

50000 Hours


Life Time



Specifications

Product Model	S65X6-T982	S75X6-T982	S86X6-T982
Display Parameters			
Size	65"	75"	86"
Response Time	8mm		
Aspect Ratio	16:9		
Display Area Size(mm)	1429(H)*804(V)	1652.5(V)*930.5(V)	1897(V)*1068(V)
Pixel Size(mm)	0.372(H)*0.372(V)	0.430(H)*0.430(V)	0.4935(H)mm*0.4935(V)
Resolution	3840 (H) ×2160 (V)		
Backlight Type	DLED		
Brightness	400 cd/m2	400 cd/m2	450 cd/m2
Contrast Ratio	4000:1	3000:1	3000:1
Refresh Frequency	60Hz		
Color Depth	1.07B (10bit)		
Color Gamut	72% NTSC(Typ.)		
View Angle	178°/178°		
Life Time	≥50000h		
Audio System			
Speaker	(8Ω 15W)*2		
Audio Channel	2.0		
Touch Specification			
Touch Technology	Infrared		
Touch Points	20		
Inductive Object	Finger, Stylus and any other non-transparent objects		
Inductive Size	Diameter≥2mm		
Touch Resolution	32768*32768		
Touch Accuracy	±1mm (≥90% Touch area)		
Response Time	≤7ms		
Operating Life	More than 60,000,000 clicks		
System Support	Windows10/Windows8/Windows7/Windows XP/ Android/Linux/Mac OS X		
Touch Panel Glass	Double side AG glass (4mm/7H)		
Android Specification			
CPU	Quad-Core A55 1.5GHz		
GPU	Mali-G53 MP2		
RAM	4GB		
ROM/FLASH	32GB		
OS.	Android 11.0		
Networks	WiFi 6 (IEEE 802.11 ac/b/g/n/a/ax, 2.4GHz/5GHz) / LAN		

X6-T982 Series Interactive Flat Panel Datasheet



I/O Port				
Front I/O	USB 3.0	*2		
	HDMI IN	*1		
	TOUCH OUT	*1		
	TYPE C	*1		
Rear I/O	HDMI IN	*2		
	USB 3.0	*2		
	TOUCH OUT	*1		
	USB 2.0	*1		
	RS232	*1		
	SPDIF	*1		
	RJ45	*2		
	PC AUDIO IN	*1		
	AUDIO OUT	*1		
	HDMI OUT	*1(Optional 1)		
	VGA IN	*1(Optional 1)		
	DP IN	*1(Optional 1)		
TYPE C	*1(Optional 1)			
Accessories				
Power Cord		*1		
Remote Control		*1		
Stylus		*2		
Wand		*1		
VESA Mount Brackets		*1(400*400mm)	*1(600*400mm)	*1(800*400mm)
Setscrews		*1(M8*25mm)		
Mobile Floor Stand		(Optional 2)		
Wireless Screen Sharing Dongle (for PC)		(Optional 3)		
OPS PC		(Optional 4)		
PC Type		Plug-in Type Intel Core Series Modular PC		
Configuration		i3 / i5/ i7		
OPS Interface		80-PIN		
Others				
Product Size(mm)	1496.5*916.2*89	1718.7*1041.4*89	1964.9*1180.3*89	
Packing Size(cm)	167*23*105	188*230*118	213*23*132	
NW.(Kg)	40.9	53.0	67.1	
GW.(Kg)	52.6	68.6	86.4	
Power Consumption	≤250W	≤280W	≤350W	
Standby Power	≤0.5W			
Power Supply	100~240V AC 50/60Hz			
Working Environment	-10°C-50°C @ 10%-90%			
Storage Environment	-20°C-60°C @ 10%-90%			